

Everase[®] Re-Stic Dry Erase Surfaces

Applications:

This product has been designed for a variety of flat vertical or horizontal interior applications such as painted dry wall, wallcovering, finished wood, painted steel, glass or other flat smooth non-porous surfaces. This product is **NOT** recommended for use on chalkboards or any curved or textured porous surfaces such as cinder block, brick, cork etc. **Contact Everase directly for a commercial grade product specifically designed to resurface chalkboards and whiteboards**.

Preparation:

Application surface should be dry, smooth, clean and free from any dust or dirt. Clean surface with a damp cloth and allow to dry before installing. If the surface is textured, for best results we recommend lightly sanding to a smooth finish. Any imperfections on the surface will show thru on the dry erase surface. If applying to a newly painted wall, please allow to fully dry before applying the dry erase surface.

The Everase[®] surface is flexible so it can be easily cut to any size desired with scissors or a utility knife. Be sure to measure before cutting and use a straight edge to ensure a perfect cut. CAUTION! Use caution when handling, cutting and installing the product to prevent injury from sharp edges.

Installation:

Installation is easy with no tools required – just unroll, peel and stick! Follow the step-by-step instructions below so you can start using your new Everase[®] Re-Stic Dry Erase Surface!



1. Unroll on a flat, clean table, then flip over so the glossy dry erase surface is face down.



2. Start peeling the paper release liner from the corner. Remove approx. 8"-12" of the liner from the top.



3. Correctly position the top edge and two corners of the dry erase surface. When proper placement desired is reached, press firmly.



4. Using a clean cloth, press firmly from side to side removing any air bubbles from under the dry erase surface.



5. Continue to remove the liner as you repeat the previous step until the film is adhered to the wall/desktop and air bubbles are removed.



 Enjoy your new Everase[®] Re-Stic Dry Erase Surface! For optimum performance please follow the specified care instructions.

EVERASE CORPORATION • 90 Industrial Drive • Ivyland, PA 18974 USA 1·800·494·5677 • WWW.EVERASE.COM



Removing and/or Repositioning:

To remove the Everase[®] Re-Stic Dry Erase Surface, slowly peel away from the top corner. Avoid ripping abruptly as this may cause damage to the surface. The adhesive is designed to peel away clean without damage to the substrate but due to the variation of surfaces we cannot guarantee removal will not result in damage. The dry erase surface should be placed back on its original backer liner to protect from dirt and dust to reuse later or discard after removing from the substrate.

The dry erase surface can be repositioned to another recommended surface if desired. By removing the dry erase surface it exposes the adhesive to dirt and dust. Special care should be taken to ensure that the area is as clean as possible. The quality of the finished product after being repositioned cannot be guaranteed.

Care and Maintenance:

For best results, use Everase[®] dry erase markers or any other reputable brand. Simply clean with water and a micro-fiber cloth. Permanent marker may be removed by tracing over any areas with a dry erase marker then wiping clean. For stubborn marks, a dry erase cleaning solution may be used. A felt eraser is not recommended. Do not use sharp objects such as ballpoint pens, metallic magnets, knives etc which could gouge and damage the writing surface. The Everase[®] surface is scratch resistant but not scratch proof.

100% Satisfaction Guaranteed!



Everase[®] provides the finest dry erase products on the market. If you are not delighted, for any reason, just simply return the product within 30 days of purchase for a replacement product or full refund of your purchase price – whichever you prefer.

To initiate a claim, the Purchaser should contact Everase[®] directly at: Everase[®] Corporation, 90 Industrial Drive, Ivyland, PA 18974, Attn: Customer Care or contact 800-494-5677 or email info@everase.com.

Love our products?

Visit Everase[®] on Amazon.com for a full list of other dry erase products including various sizes and printed options as well as dry erase accessories. Contact Everase[®] directly for custom sizes and custom printed Re-Stic Dry Erase Surfaces! If you can imagine it, we can create it!

Please contact Everase directly with any questions regarding installation or care and maintenance of our dry erase products! 800-494-5677 or info@everase.com

Updated 9/1/2016