

TECHNICAL PERFORMANCE OF EVERASE® SURFACES

Our specifically engineered dry erase composite surface provides excellent printability and erasability in an impervious formulation. Everase offers the best quality features of scratch, chemical, stain, heat, and wear resistance and remains unsurpassed when compared and contrasted with our competition.

FEATURES	PROPERTY	RESULT
WRITEABILITY	Use of any dry erase, fluorescent, semi-permanent, and permanent markers and crayons will not damage the Everase surface.	Better than comparable products
ERASABILITY	Dry erasability using Boone 30 day test method	5 lbs/3 rubs or better with all tested dry erase markers*
	Gloss at 60 degrees using BYK Gardner / Micro-TRI-Gloss Test Method	100%
VISIBILITY	Excellent contrast compared to chalkboards. Allows for multi-color presentations	Excellent
PRINTABILITY	Excellent marker pen printability and erasability	Better than comparable products
	Non-ghosting, non-yellowing product	
	Both permanent and dry erase markers can be used for permanent and temporary information but then cleaned easily	
DURABILITY	Scratch resistance using Hoffman Scratch Test	700
	Hardness - Pencil using ASTM D3363-74	7H
WEARABILITY	Abrasion resistance using Taber Abrasion / 500 g - CS-10 Wheel	500 cycles
	Wear resistance using BYK Gardner Sled	5000 cycles
STAIN RESISTANCE	NEMA LD3-2000 3-4 Stain Resistance Report	Coffee, Tea, Mustard, Black permanent marker, #2 Pencil, Wax Crayon, Lipstick: 0 (No effect)
CHEMICAL RESISTANCE	ASTM D-1308 Method B-24 Report	Glass Cleaner - No stain Rubbing alcohol - No stain MEK (Methyl Ethyl Ketone) - No stain



These lab results are provided as a service only. All products are sold upon condition that the purchaser shall make their own tests and judgments. No warranty of merchantability or fitness for any purpose is implied by these test results, neither does this constitute the seller's product specifications. Everase® is a Registered Trademark. * Test Method and Results are available upon request.

EVERASE CORPORATION • 90 Industrial Drive • Ivyland, PA 18974 USA
1-800-494-5677 • Fax: 215-323-4135 • info@everase.com • www.everase.com

EVERASE® CORPORATION

Ten Year Limited Warranty

1. Everase Corporation (“Everase”) warrants to the original purchaser (the “Purchaser”) that the Everase Whiteboard product (the “Product”) sold to Purchaser will be free from manufacturing defects and, under normal use and service, will not chip, crack or lose its original erasability properties for a period of ten (10) years from date of original purchase.

2. The above warranty applies solely to Products that have been properly installed, and maintained in accordance with Installation Instructions as well as the Care and Maintenance Procedures provided by Everase at the time of purchase. Purchaser’s sole remedy in the event of breach of the above warranty shall be repair or replacement, at the option of Everase, of the defective Product. Everase shall not be responsible for any costs other than actual repair or replacement of any defective Product, including removal, shipping or reinstallation costs, or other incidental expenses. Everase reserves the right to make such inspections as may be necessary to determine the cause of defect and eligibility for warranty coverage.

3. To initiate a claim for warranty, the Purchaser should contact Everase directly at: Everase Corporation, 90 Industrial Drive, Ivyland, PA 18794, Attn: Customer Care. Full details of the defect, including any photographs to depict the condition, should be included for prompt resolution of any claim.

4. EVERASE MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO THE PRODUCTS, AND EVERASE SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. NO OTHER REPRESENTATION OR WARRANTY, INCLUDING BUT NOT LIMITED TO STATEMENTS OF QUALITY, SUITABILITY FOR USE OR PERFORMANCE, WHETHER MADE BY EMPLOYEES OF EVERASE, DISTRIBUTORS OR ANY SALES AGENT, SHALL BE CONSIDERED A WARRANTY BY EVERASE FOR ANY PURPOSE OR CREATE ANY LIABILITY OF EVERASE.

